



# Elastomer Jaw Couplings

## RINGFEDER® TNS S-BT

### Coupling with standard hub and brake drum



Identifier	Size	A	SB	T <sub>KN</sub>	T <sub>Kmax</sub>	T <sub>BR</sub>	n <sub>max</sub>	d <sub>1kmax</sub>	d <sub>2kmax</sub>	D <sub>1</sub>	D <sub>2</sub>	C <sub>1</sub>	C <sub>2</sub>	C <sub>B</sub>
		mm	mm	Nm	Nm	Nm	1/min	mm	mm	mm	mm	mm	mm	mm
WS0510-200	100	200	75	130	390	260	4200	48	42	105	75	49,5	49,5	14
WS0512-200	125	200	75	250	750	310	4200	55	55	126	85	56,5	56,5	20
WS0514-200	145	200	75	400	1200	730	4200	65	65	145	95	61	61	21
WS0514-250	145	250	95	400	1200	730	3400	65	65	145	95	61	61	13
WS0517-250	170	250	95	630	1900	1200	3400	85	85	170	120	75	75	27
WS0517-315	170	315	118	630	1900	1350	2700	85	85	170	120	75	75	13
WS0520-315	200	315	118	1100	3300	2450	2700	95	95	200	135	99	99	38
WS0520-400	200	400	150	1100	3300	2650	2100	95	95	200	135	99	99	26
WS0523-400	230	400	150	1700	5150	3800	2100	105	105	230	150	110	110	36
WS0523-500	230	500	190	1700	5150	3800	1700	105	105	230	150	110	110	25
WS0526-500	260	500	190	2650	7950	9000	1700	125	125	260	180	112,5	112,5	25
WS0530-630	300	630	236	3900	11700	10500	1360	140	140	300	200	131,5	131,5	20
WS0530-710	300	710	265	3900	11700	11000	1200	140	140	300	200	131,5	131,5	0
WS0536-630	360	630	236	6500	19500	26000	1360	150	150	360	210	172	172	51
WS0536-710	360	710	265	6500	19500	26000	1200	150	150	360	210	172	172	34
WS0540-710	400	710	265	8900	26700	35000	1200	160	160	400	225	163,5	163,5	30

For further information see chapter „Introduction“ as well as chapter „Elastomer Jaw Couplings RINGFEDER® TNS Basic information“ in the Product Paper & Tech Paper „RINGFEDER® Elastomer Jaw Couplings“

To continue see next page

### Elastomer Jaw Couplings RINGFEDER® TNS S-BT

Identifier	Size	C <sub>B</sub>	L	L <sub>2</sub>	L <sub>3</sub>	E	F <sub>E</sub>	H <sub>3</sub>	d <sub>be</sub>	Screws ISO 4762 - 8.8				G <sub>wub</sub>
										n <sub>Sc</sub>	D <sub>G</sub>	L <sub>Sc</sub>	T <sub>A</sub> <sup>1)</sup>	
		mm	mm	mm	mm	mm	mm	mm	mm		mm	mm	Nm	kg
WS0510-200	100	14	125	37,5	39,5	3	+ 2,0	20	42	6	8	20	25	9,4
WS0512-200	125	20	145	44	45,5	3,5	+ 2,5	25	54	6	8	20	25	12,0
WS0514-200	145	21	160	47,5	48,5	4	+ 2,5	30	66	6	10	25	49	15,2
WS0514-250	145	13	160	47,5	48,5	4	+ 2,5	30	66	6	10	25	49	19,8
WS0517-250	170	27	190	60,5	62	5	+ 3,0	30	90	8	10	25	49	26,7
WS0517-315	170	13	190	60,5	62	5	+ 3,0	30	90	8	10	30	49	36,1
WS0520-315	200	38	245	79,5	84	6	+ 3,0	35	100	8	12	30	85	48,0
WS0520-400	200	26	245	79,5	84	6	+ 3,0	35	100	8	12	35	85	64,6
WS0523-400	230	36	270	88,5	93	7	+ 3,5	35	115	10	12	35	85	75,8
WS0523-500	230	25	270	88,5	93	7	+ 3,5	35	115	10	12	35	85	103,1
WS0526-500	260	25	285	88,5	91	7	+ 4,0	45	150	10	16	40	210	121,6
WS0530-630	300	20	330	107,5	110,5	7	+ 4,0	50	162	10	16	45	210	199,4
WS0530-710	300	0	330	107,5	110,5	7	+ 4,0	50	162	10	16	50	210	255,9
WS0536-630	360	51	417	140	144	8	+ 4,0	55	215	12	20	50	425	261,0
WS0536-710	360	34	417	140	144	8	+ 4,0	55	215	12	20	55	425	304,5
WS0540-710	400	30	400	137	141	7,5	+ 4,0	55	250	14	20	50	425	317,6

### Explanation

<b>A</b> = Max. outer diameter	<b>D<sub>2</sub></b> = Outer diameter hub	<b>n<sub>Sc</sub></b> = Quantity of screws
<b>SB</b> = Disc width	<b>C<sub>1</sub></b> = Guided length in hub bore	<b>D<sub>G</sub></b> = Thread
<b>T<sub>KN</sub></b> = Nom. Transmissible torque	<b>C<sub>1</sub></b> = Guided length in hub bore	<b>L<sub>Sc</sub></b> = Screw length
<b>T<sub>Kmax</sub></b> = Max. transmissible torque of the coupling	<b>C<sub>B</sub></b> = Brake disc distance	<b>F<sub>Sc</sub></b> = Screw strength class
<b>T<sub>BR</sub></b> = Brake torque	<b>L</b> = Total length	<b>T<sub>A</sub></b> = Max tightened torque of the clamping screws
<b>n<sub>max</sub></b> = Max. rotation speed	<b>L<sub>2</sub></b> = Length on the hub	<b>G<sub>wub</sub></b> = Weight, unbored
<b>d<sub>1kmax</sub></b> = Max. bore diameter d <sub>1</sub> with keyway acc. to DIN 6885-1	<b>L<sub>3</sub></b> = Length	
<b>d<sub>2kmax</sub></b> = Max. bore diameter d <sub>2</sub> with keyway acc. to DIN 6885-1	<b>E</b> = Gap width between left and right component	
<b>D<sub>1</sub></b> = Outer diameter	<b>F<sub>E</sub></b> = Tolerance of the gap width E	
	<b>H<sub>3</sub></b> = Length of damping module	
	<b>d<sub>be</sub></b> = Inner diameter elastic intermediate ring	

### Ordering example

Identifier	Size	d <sub>1k</sub>	d <sub>2k</sub>	Further details
WS0523-400	230	105	105	*

<sup>1)</sup> Without any other specification, we deliver as a standard: with set screws and keyway acc. to DIN 6885-1, keyway side fit P9, bore tolerance H7

Further information on  
**RINGFEDER® TNS S-BT**  
 on [www.ringfeder.com](http://www.ringfeder.com)

#### Disclaimer of liability

All technical details and notes are non-binding and cannot be used as a basis for legal claims. The user is obligated to determine whether the represented products meet his requirements. We reserve the right carry out modifications at any time in the interests of technical progress.